



# NEW Dust Extractor

*Vacuum assisted sanding kit system  
with immersion separator for the  
automotive repair industry*

## Features

- Fully integrated automatic On/Off switch allows the electrically operated vacuum cleaner to be controlled by a pneumatic hand tool
- HEPA Filter - included with an efficiency of 99.995% on 0.3 micron. Tested: IEST RP-CC001.3. H14 by MPPS method as per EN 1822
- CSA Certified



Detachable oil/water tank for easy  
emptying of recovered materials

# Optional Accessories



**20' Suction/Air Supply Hose**  
made of static conductive PVC



**Coalescing Filter Element**  
assembly complete with housing.



**Wye Connector** allows two suction hoses to be used on one vacuum at the same time

## Specifications

### AS-400/85L (OL) SK HEPA Performance

Vacuum Pressure	107" H <sub>2</sub> O
Air Flow	110 CFM
Phase	Single
Horse Power	1.6 HP
Amperage	10.5 AMP
Wattage	1200 W
Hertz	60 Hz
Voltage	120 V
Noise Level	72 dB
Weight	220 lbs.
Dimensions	24" x 41" x 70" (high)
Plug	Included

### EC-15 (IT-85L) SK HEPA Immersion Separator

Filtration System	Immersion Separator
Dry Recovery	1.3 gallons of dust into 7.9 gallons of neutralizing liquid



©2015 VEHICLE SERVICE GROUP™  
Printed in the U.S.A. All Rights Reserved. Unless otherwise indicated, CHIEF AUTOMOTIVE TECHNOLOGIES, VEHICLE SERVICE GROUP™, DOVER and all other trademarks are property of the Dover Corporation and its affiliates. Chief Automotive Technologies reserves the right to alter product specifications and/or package components without notice, excluding changes to components subject to FCC & IC regulations. Dust Extractor 04/15



automotive technologies

**1-800-445-9262**

[www.chiefautomotive.com](http://www.chiefautomotive.com)

Improve the speed, quality and profitability of every repair you make. Contact your local distributor or call Chief Automotive Technologies today.