

MULTIMIG 511

Part #EL900012 with Push-Pull Torch
Part #EL900011 with Standard Aluminum Torch
Part #EL900070 with Brazing Torch

A push-pull torch designed specifically to optimize aluminum welding.
Synergic pulsed welder with full set of welding programs!

Welding and brazing of aluminum alloys, galvanized sheet metal, stainless, and high-strength steel.

The push-pull system has an up-down digital current adjust at your finger tip - enables real-time control of welding process. Programmable options are available to customize the unit operation.

Features

- OEM required synergic pulsed technology - includes a complete set of programs
- Inverter technology enables precision control of output power
- **GREEN technology** - Integrated Power Factor Correction (PFC) technology reduces operating costs.

INCLUDES Built-in cart for easy welder handling and storage for gas cylinder



#EL900012 with Push-Pull Torch



Push-pull torch



Standard torch



1-800-445-9262

www.chiefautomotive.com

Improve the speed, quality and profitability of every repair you make. Contact your local distributor or call Chief Automotive Technologies today.



©2018 VEHICLE SERVICE GROUPSM Printed in the U.S.A. All Rights Reserved. Unless otherwise indicated, CHIEF AUTOMOTIVE TECHNOLOGIES, VEHICLE SERVICE GROUPSM, DOVER and all other trademarks are property of the Dover Corporation and its affiliates. Chief reserves the right to alter product specifications and/or package components without notice, excluding changes to components subject to FCC & IC regulations.

SPECIFICATIONS

Single Phase Input	230V 50/60Hz + 15% to -20%
Supple Fuse Rating (slow blow)	30A
Input Power	5.7 KVA 20% 4.1 KVA 60% 3.2 KVA 100%
Current Adjustment Range	20A to 200A
Duty Cycle (10 min 40°C) According to IEC 60974.1	200A 20% 140A 60% 120A 100%
Stepless Regulation	Electronic
Standard Supplied Synergic Programs	0.6/.08/0.9/1.0 Fe, Alu 0.6/0.8/0.9/1.0/1.2 AL 0.8/0.9 Stainless Steel, CuSi3 0.9 Flux core
Max. Wire Spool Size	Ø 200 mm / 5kg Ø 300 mm / 15kg
Protection Class	IP 23 S
Weight	99.2 lbs
Dimensions Inches	18.9 x 33.7 x 32.5h