

Easy to use, lightweight and highly efficient

This riveting tool allows your technicians to complete all common riveting operations in thin sheet metal structures in record time.



Perfect Rivet Every Time.

Chief Rivet Guns allow you to quickly restore cars, trucks and heavy duty vehicles back to factory specifications with a professional and seamless finish. With durable construction, a variety of attachments the rivet guns can handle any job you throw at them.

Specifically developed for riveting sheet metal in the autobody repair field, this rivet gun is a pneumatic-hydraulic system which easily adaptsvarious attachments for different applications. The hydraulic pump is pneumatically driven. The pressure intensifier, with a ratio of 100:1, delivers hydraulic output pressure of 8702 psi (600 bar) with input pressure of only 87 psi (6 bar). When the equipment's preset final pressure is reached, the pump stops and maintains constant pressure, using a pneumatically controlled pressure regulator.

Features, Advantages, Benefits

Universal - allows for attachments for various applications: Riveting / Punching / Pressing Out / Calibrating

Highly efficient - pressure ratio of 100:1

Precise control over strength of impact

Sturdy construction with low maintenance

The basic tool kit contains the pneumo-hydraulic pressure intensifier a hydraulic gun, an NB 40 rivet clamp and a fully equipped UN 2.0 Riveting Tool Kit.



BASIC RIVET GUN KIT







Hydraulic Gun **HP 35 UN**



Pressure Intensifier PNP90



Riveting Tool Kit **Locking Bolts**



Case

1x Pressure intensifier PNP90 1x Hydraulic gun HP 35 Un

1x Rivet clamp NB 40

- Length x Width x Height -4-11/64 x 1-49/64 x 6-17/64" (106 x 45 x 159mm)
- Weight 3.4 lbs. (1.5 kg)
- Clamp Opening 3-5/32" (80mm)
- Opening Depth 1-37/64" (40mm)

1x Riveting tool kit RIVKIT - UN 2.0

- Setting / closed head 1/8" (3mm) rivet
- Setting / closed head 13/64" (5mm) rivet
- Setting / closed head, flow form rivet
- Punch and calibration mandrel / die
- Extraction mandrel / die
- Replacement elastomer rings
- Set of mounting tools
- Spacing adaptor 2x Locking bolts

Optional Accessories



Rivet Clamp NB 115 #CHR2204



Rivet Clamp NB 230 #CHR2203

Specifications - Rivet Gun Technical data Pump PNP90 UN 2.0 Length x Width x Height 12-63/64 x 9-1/16 x 8-25/64" (without hoses, including handle) (330 x 230 x 213mm) Weight (without hoses) 17.1 lbs. (8kg) Max input pressure 6 bar / 87 PSI 600 bar / 8702 PSI Max operating pressure

Length x Width x Height (including handle)	9-11/16 x 1-31/32 x 4-9/64" (246 x 50 x 105mm)
Max operating pressure	600 bar / 8702 PSI
Travel	19/32" (15mm)

Hydraulic gun HP 35 UN

RIVET CLAMP NB 115	8-25/64 x 1-47/64 x 8-21/32"
Length* x Width x Height	(213 x 44 x 220mm)
Weight*	6.9 lbs. (3kg)
Clamp Opening	3-5/32"(80mm)
Opening Depth	4-17/32" (115mm)
DIVET OF VMD VID 330	14 21/64 v 1 40/64 v 12 4E/64"
	14-21/64 x 1-49/64 x 13-45/64" (364 x 45 x 348mm)
Length* x Width x Height	7
Length* x Width x Height Weight*	(364 x 45 x 348mm)
RIVET CLAMP NB 230 Length* x Width x Height Weight* Clamp Opening Opening Depth	(364 x 45 x 348mm) 20.15 lbs. (9.5kg)



Improve the speed, quality and profitability of every repair you make. Contact your local distributor or call Chief Automotive Technologies today.



©2017 VEHICLE SERVICE GROUPSM

Printed in the U.S.A. All Rights Reserved, Unless otherwise indicated, CHIEF AUTOMOTIVE TECHNOLOGIES, VEHICLE SERVICE GROUPSM, DOVER and all other trademarks are property of the Dover Corporation and its affiliates. Chief Automotive Technologies reserves the right to alter product specifications and/or package components without notice, excluding changes to components subject to FCC & IC regulations.